

---

# TANNOY REVOLUTION XT-6 GLOSS WHITE GW BOOKSHELF SPEAKER



**VIEW ALL PRODUCTS FROM THIS**

**BRAND:** Tannoy

**Product Code:** REVOLUTION XT-6 GLOSS  
WHITE GW

**Price: R13,247.00**

## **Description**

### **TANNOY REVOLUTION XT-6 GLOSS WHITE GW BOOKSHELF SPEAKER**

Combining a 150 mm (6 inch) multi-fibre cone with a 25 mm Linear PEI dome and benefitting from the Torus-Ogive waveguide the REVOLUTION XT 6 driver is coupled with a crossover using low loss laminated core inductors and audiophile components throughout.

The 10.8 litre cabinet has REVOLUTION XT's signature trapezoid shape and is uniquely fitted with a miniature plinth in keeping with the larger floorstanding models. The plinth serves to add low-down mass to the design, affording highly stable placement on stands or shelves for the most accurate acoustic reproduction. Heavily constructed and extensively braced, the cabinet has exceptionally low colouration further enhancing its ability to communicate nuances and emotion of music. The REVOLUTION XT 6 is an incredibly accurate mini-monitor for those who appreciate music presented with utmost detail and texture.

## **FEATURES**

- 2 way stand mount loudspeaker for small to medium sized rooms
- Dual Concentric driver technology provides class-leading coherence and point-

source imaging

- 6" Dual Concentric driver delivers unrivalled musical articulation and outstanding dynamics
- Highly efficient 89 dB/Watt sensitivity and 240 Watt peak power handling deliver breath-taking dynamics and realism
- Magnetic grille mounts provide a smooth and uncluttered front baffle appearance
- New Dual Omnimagnet motor delivers smoother bass performance with exceptional transient attack
- HF and LF drivers share single Omnimagnet optimising phase coherence for natural and expansive sound
- Innovative shallow Torus Ogive waveguide allows rapid wavefront expansion improving high frequency directivity
- Non-parallel trapezoidal cabinet disperses internal standing waves and reflections for low colouration
- Internal bracing provides extra cabinet rigidity for exceptionally tight and controlled bass
- Down-firing port reduces room boundary effects and facilitates easy loudspeaker placement
- Integral plinth provides exceptional stability

## **Performance**

### **Recommended Amplifier Power (Watts RMS)**

25 - 120

### **Continuous Power Handling (Watts Peak RMS)**

60

### **Peak Power Handling (Watts)**

240

### **Sensitivity (2.83 Volts @ 1m)**

89 dB

### **Nominal Impedance (Ohms)**

8

### **Frequency Response (-6dB)**

46 Hz - 32 kHz

## **Drive Units**

## **Dual Concentric™ High Frequency**

25 mm (1") Linear PEI dome with Torus Ogive WaveGuide and Omnimagnet technology

## **Dual Concentric™ Low Frequency**

150 mm (6") multi-fibre paper 44 mm (1.75") voice coil

## **Crossover**

### **Crossover Frequency**

1.8 kHz

### **Crossover Type**

Passive low loss 2nd order low pass, 1st order high pass

## **Construction**

### **Enclosure Type**

Downwards ported reflex

### **Volume**

10.8 l (0.38 cu. ft.)

### **Dimensions H x W x D (incl. plinth)**

400.5 x 221 x 302 mm (15.8 x 8.7 x 11.9")

### **Net Weight**

7.5 kg (16.4 lbs)

## **Product Gallery**

